

the best solutions always from



since 1972  
2515

PAT a multi-brand company



The garage sectional overhead sandwich door panel with finger protection is 4mm thick, comprises of 2 x galvanized white metal sheets with polyurethane thermal insulation. The standard colour is white. Other colours can be ordered at extra costs. The low overhead profile rails and hinges are in standard white colour.

ตัวอย่างงานติดตั้งต่างๆ



# การจาดอร์อัตโนมัติ GarageDOOR



อุปกรณ์มอเตอร์ ระบบควบคุม รีโมท นำเข้าโดย PAT จาก LIFTMASTER ผู้ผลิตมอเตอร์สำหรับประตู GARAGE DOOR อันดับหนึ่งของอเมริกาและของโลก

ประตูจาดอร์เป็นประตูแบบเปิดยกขึ้นและพับเป็นชั้น ๆ บานประตูเป็นเหล็ก galvanized แบบแซนวิชหนา 4 มม. มีฉนวน polyurethane กันความร้อนอยู่ตรงกลาง แต่ละชั้นจะเก็บขอบโค้งเพื่อป้องกันการชนนิ้วมือเวลาพับ สีสมาตรฐานคือสีขาว แต่สามารถทำสีได้ตามต้องการและเพิ่มค่าทำสี

CHAMBERLAIN

## LiftMaster

### know you made the right choice

built and backed by Chamberlain

Chamberlain is the world's largest manufacturer of garage door openers and delivers a quality product which you can depend on. No other manufacturer builds garage door openers like Chamberlain. For years of trouble free performance, every model undergoes extensive computer testing before it leaves our factory. When you demand the best, LiftMaster™ Garage Door Openers give you everything you want and more including the very latest safety, security and convenience features. Chamberlain is an ISO9001 certified manufacturer that designs and develops products to meet the latest EN and IEC product standards. As a result you can be confident that you are buying the best garage door opener on the market.

LM 60

- \* 100W DC motor
- \* electronic limits
- \* 2-year warranty



5580

- \* 400W AC motor
- \* mechanical limits
- \* 2-year warranty



automatic beam force sensing



rolling code remote control



manual release handle

Feature	Lm60	5580
Pulling force	600N	800N
Motor	24V DC	230V AC
Force Sensing	Yes	Yes
Soft-start/soft-stop	Yes	No
Drive	LM60K-chain LM60R-belt	Chain
Rail	4-pc steel C-rail	steel C-rail
Rail in separate carton	No	Yes
Radio frequency	433.92MHz	433.92MHz
Receiver type	Super-heterodyne	Super-heterodyne
Memory registers	12	12/1/1
Code	Rolling	Rolling
Remote controls	1x3-channel mini	1x3-channel mini
Wall control	Illuminated push button	Illuminated push button
Auto close	No	No
24V DC, 240mA power terminal	No	No
Rated door area	10.7m <sup>2</sup>	13.5m <sup>2</sup>
Rated door weight	90kg	110kg