




FAAC 402 hydraulic operator for residential swing gates with single-leaf length of 1.8 m (402 CBC) and 3 m (402 SBS)


Model	Use	
	Single leaf max length (m)	Use frequency (cycles/hour)
402 CBC	1.80	55
402 SBS	3.00	55

Technical specifications	402 CBC	402 SBS
Power supply	230 V~ (+6% -10%) 50 (60) Hz	
Absorbed power	220W	
Absorbed current	1 A	
Motor rotation speed	1400 rpm	
Rod extension speed	1.3 cm/s	1 cm/s
Pump flow rate	1 l/min.	0.75 l/min
Traction and thrust force	0-500 daN	0-690 daN
Operating ambient temperature	-20 °C + 55 °C	
Thermal protection on motor winding	120 °C	
Weight	6.5 kg	
Type of oil	FAAC OIL XD 220	
Protection class	IP 55	

Dimensions



INSTALLATION LAYOUT



Low voltage cabling	Power cabling (230V)
(A) <ul style="list-style-type: none"> 3 cables 3x0.5 1 cable 2x0.5 	(B) <ul style="list-style-type: none"> 2 cables 3x1.5+T 1 cable 2x1.5+T 1 cable 2x1.5

N.B.: Cable diameters in mm'

