

NEW



www.faacgroup.com

FAAC

Faac spa

Via Benini, 1 - 40069 Zola Predosa (BO) - Italy
Tel. +39 051 61724 - Fax. +39 051 758518 - info@faac.it



S700H

Underground hydraulic operator (24V) for swing gates
with single leaf max length 4 m and single leaf max weight 800 kg

FAAC

S700H

Underground hydraulic operator (24V) for swing gates with single leaf max length 4 m and single leaf max weight 800 kg

Two handles help to install

Positive Stop Integrated

Integrated bus rotating magnetic encoder

24V Electric Motor

Hydraulic release device

- > Cataphoresis treated self-supporting steel box (welding to pillars allowed)
- > Stainless steel cover
- > Independent transmission system

Lever release system



CONTROL BOARD E024

- > Functions programming through leds and push-buttons
 - > Bus-controlled "Encoder" management (speed, end travel deceleration, anti-crushing function - EN standard)
 - > Electric lock management
- > Hydraulic 24 V technologic solution to integrate the advantages of both technologies: solidity, performances, reliability, silence, speed control, anti-crushing security,...



TECHNICAL SPECIFICATIONS	CBAC Operator	SB Operator
Power supply		230 Vac
Absorbed power		120 W
Electric Motor		24 Vdc
Work frequency		50 hz
Protection class		IP 67
Type of oil		FAAC HP OIL
Operating ambient temperature		-20° C ÷ +55° C
Use Frequency		100%
Hydraulic shut-down facility	Supplied	Not supplied
Pump flow-rate		0,5 l/min
Max torque		575 Nm
Angular speed		4,8 °/sec
Max opening angle		110°/180°
Type of slow down		Electronic
leaf max length	1,8 m	4 m
Leaf max weight		800 kg